

SG6230, SG6240 Series Mobile Cylinder Carts

Mobile Cylinder Carts are designed to provide safe transport for multiple cylinders. They are made of welded 11 gauge steel construction and finished with impact resistant, electrostatically applied powder coat semi-gloss paint. All models use 1½" polypropylene straps with steel non-slip cinch buckles, the same as used in on our two (Model 6207) and three (Model SG6208) cylinder wall brackets. The carts are shipped partially assembled and can ship UPS for freight savings.

Four Cylinder Wheeled Cart (Part No. SG6230) –

These carts are designed to safely transport four cylinders up to 12" OD. The cart features four, 4" swivel caster wheels (two with wheel brakes) and a push handle to provide for good load control. Two polypropylene straps are supplied at each cylinder station to safely secure cylinders. Approximate size: 24" x 40" x 36" and weight: 155 lbs.

Six Cylinder Wheeled Cart (Part No. SG6231) –

These carts are designed to safely transport six cylinders up to 12" OD. The cart features four, 4" swivel caster wheels (two with wheel brakes) and a push handle to provide for good load control. Two polypropylene straps are supplied at each cylinder station to safely secure cylinders. Approximate size: 24" x 52" x 36" and weight: 185 lbs.

Four Cylinder Forklift Portable Cart (Part No. SG6240) –

These carts are designed to be carried by a forklift to safely transport four cylinders up to 12" OD. The cart features two-way fully enclosed forklift channels to provide for safe load control. Two polypropylene straps are supplied at each cylinder station to safely secure cylinders. Approximate size: 24" x 40" x 30" and weight: 125 lbs.



4 Cylinder Wheeled Cart



4 Cylinder Forklift Portable Cart

Models SG6220, SG6221, SG6222, SG6223 Cylinder Safety Caps

These locking caps ensure safety and reduce the possibility of misuse and vandalism with compressed gas cylinders by limiting access to the main cylinder control and regulator attachment. They are designed to fit most North American high and low pressure cylinders and meet standards of DOT and CGA by attaching securely to the collar of the cylinder. Cylinder Safety Caps are available with fine and coarse thread configurations. Stocked units are enamel painted in safety yellow and are supplied with a weather resistant, keyed brass padlock.

Table I

Part No.	For Cylinder Style	For Collar Thread Style	Collar Threads (per in.)	Dimensions	Weight (lbs.)
SG6220	High Pressure	Fine	11	6½" x 3⅛"	4
SG6221	High Pressure	Coarse	7	6½" x 3⅛"	4
SG6222	Low Pressure	Fine	11	6½" x 3½"	4
SG6223	Low Pressure	Course	7	6½" x 3½"	4



Locked Safety Cap